



[Home](#)

[What is a Ground Source Heat Pump?](#)



[Products](#)

[Construction Features](#)

[Advantages & Benefits](#)

[Training](#)

[Technical Support](#)

[Newsletters](#)

[Company Information](#)

[Testimonials](#)

[Contact Us](#)



ALL STAINLESS STEEL CABINET WITH A LIFETIME WARRANTY

[Products](#) >> Dual Compressor Upflow and Side Discharge

**Dual Capacity Water to Air
HCD48 thru HCD144
(4 thru 12 ton in 2 ton
increments):**

- Dual Compressor Water to Air Units
- Single Package
- Available in Upflow and Side Discharge
- Right or Left Return
- 10, 15, and 20 kW Internal Strip Heat Options
- Domestic Water Heating Option
- Compressors May Be Staged for Dual Heating and Cooling Out-Put
- Fan Out-Put Remains Constant
- 208/230 Volt, Direct or Belt Driven Fans (optional)
- High Heating Out-Put
- All Panels Removable for Easy Service



All models in this section qualify for Energy Star except the 6 & 12 ton units. Energy Star requires the desuperheater option to qualify.

Forced Air (Water to Air) Dual Compressor

ARI 330 Performance Ratings (ISO 13256-1)
Based on 32° entering water temperature in heating mode and 77° entering water temperature in cooling mode.

(Includes Pump Penalties)

Model #	CFM	GPM	BTU/hr Heating	COP	BTU/hr Cooling	EER
HCD48	1600	12.0	42,600	3.4	51,600	15.1
HCD72	2400	18.0	64,000	3.4	77,000	15.0
HCD96	3200	24.0	83,600	3.4	100,800	15.0
HCD120	4000	28.0	112,400	3.4	130,600	15.0
HCD144	4500	30.0	122,000	3.1	145,600	13.5

World's Best Built Heat Pump

E-mail: heatpump@energy-dynamics.com

Copyright © Energy Dynamics 1997-2003; All Rights Reserved.