



**THE FUTURE
OF WATER HEATING**

COMMERCIAL WATER HEATER

[Stone Story](#) | [Electric Water Heaters](#) | [Indirect Water Heaters](#) | [Solar Water Heater](#) | [Custom Tanks](#) | [Commercial Tanks](#) | [Range Boilers](#)

Hydrastone Lining

a seamless one half inch

thick lining which has proven to be the most effective method of preventing tank failure due to corrosion.

Bronze Fittings

at all water openings eliminates corrosion due to dissimilar metals. No dielectric unions.

Immersion Controls

All models equipped with immersion aquastat(s) and high limit cut-out for accurate temperature sensing and safety.

Two Models

80 and 120 gallon capacity, from 6kw up to 54kw output. Wiring for 208/240/277/480 volts, single or three phase.

Custom Options

Available Call 1-800-282-8446



Dense Urethane Foam Insulation significantly reduces standby heat loss and increases energy savings.

Plastic Jacket

Rust free, light weight all plastic outer jacket. Easy to clean, attractive finish, no maintenance

Cold Water Inlet Diffuser

introduces cold water at the bottom of the tank and prevents turbulent mixing with heated; this insures desired layering of

hot water through
the tank.

COMMERCIAL ELECTRIC WATER HEATERS

MODEL	WATTAGE	HEIGHT	DIAMETER
S 120 A4-12	12 Kilowatts	69	28
S 120 A4-18	18 Kilowatts	69	28
S 120 A4-24	24 Kilowatts	69	28
S 120 A4-30	30 Kilowatts	69	28
S 120 A4-36	36 Kilowatts	69	28
S 120 A4-48	48 Kilowatts	69	28
S 120 A4-52	52 Kilowatts	69	28

* Price includes appropriate T&P Relief Valve (Watts 40XL)

Dimensions are all for 120 gallon tanks.

Also available in 80 and 100 gallon sizes at the same prices

Cabinet Dimensions: add 12" width x 50" high x 8" deep

Insulation: 2" urethane foam

Freight: F.O.B. Salisbury MA.

Terms: 2% 10, Net 30 Days

Limited Warranty: 5 YEARS

[Home Page](#) | [Vaughn Corporation History](#) | [Vaughn News](#) | [Vaughn Products](#) | [Turnkey Program](#) |
[Connect With Vaughn](#)

Vaughn Manufacturing Corporation, 26 Old Elm St., PO Box 5431, Salisbury, Massachusetts 01952-5431
Telephone (978) 462-6683 | FAX (978) 462-6497

© [Copyright 1997](#) © Vaughn Manufacturing Corporation | Maintained by  [EnSite Corp.](#)
[Contact Vaughn](#) | [Contact Webmaster](#)