



**THE FUTURE
OF WATER HEATING**

SOLAR WATER HEATER

[Stone Story](#) | [Electric Water Heaters](#) | [Indirect Water Heaters](#) | [Solar Water Heater](#) | [Custom Tanks](#) |
[Commercial Tanks](#) | [Range Boilers](#)

Hydrastone Lining

a seamless one half inch thick lining which has proven to be the most effective method of preventing tank failure.

Bronze Fittings

at all water openings eliminates corrosion due to dissimilar metals. No dielectric unions.

Dense Urethane Foam Insulation

completely surrounds the tank to significantly reduce heat loss and increase energy savings (R-16 insulation value)

[Removable Heat Exchanger](#)

Conveniently



Heat Trap

specifically designed hot water outlet pipe placed within the foam insulation to prevent unnecessary heat loss.

Plastic Jacket

Rust free, light weight all plastic outer jacket. Easy to clean, attractive finish, no maintenance

Cold Water Inlet Diffuser

introduces cold water at the bottom of the tank and prevents turbulent mixing with heated; this insures desired layering of hot water through the tank.

located and simple
8 bolt flange
design for ease of
installation and
service. This
superior design
allows for periodic
cleaning of coil to
maintain maximum
performance.

**Limited
Warranty: 7
Years Residential
Models
5 Years -
Commercial
Models**

SINGLE WALL HEAT EXCHANGER

MODEL	CAPACITY	HEIGHT	DIAMETER
S 65 SR HX20	65	47 7/8	26
S 80 SR HX20	80	58	26
S 120 SR HX20	115	69	28

DOUBLE WALL HEAT EXCHANGER

MODEL	CAPACITY	HEIGHT	DIAMETER
S 65 SR HX20DW	65	47 7/8	26
S 80 SR HX20DW	80	58	26
S 120 SR HX20DW	115	69	28


DIRECT EXCHANGE

MODEL	CAPACITY	HEIGHT	DIAMETER
S 80S	80	58	26
S 120S	115	69	28

ELECTRICAL ELEMENTS: 4500 WATT, 240
VOLT (LOW WATT DENSITY) is standard
Other Wattages available by request.
All 120 GAL. and Direct Exchange Tanks have 2
elements
All OTHER TANKS HAVE ONE ELEMENT.
INSULATION:S=2 Inches Urethane Foam
FREIGHT:F.O.B. Salisbury MA.
TERMS:2% 10 NET 30 Days
LIMITED WARRANTY 7 YEARS

[Home Page](#) | [Vaughn Corporation History](#) | [Vaughn News](#) | [Vaughn Products](#) | [Turnkey Program](#) |
[Connect With Vaughn](#)

Vaughn Manufacturing Corporation, 26 Old Elm St., PO Box 5431, Salisbury, Massachusetts 01952-5431
Telephone (978) 462-6683 | FAX (978) 462-6497

© Copyright 1997 © Vaughn Manufacturing Corporation | Maintained by  [EnSky Corp.](#)

[Contact Vaughn](#) | [Contact Webmaster](#)
