



Home

What is a Ground Source Heat Pump?



Products

Construction Features

Advantages & Benefits

Training

Technical Support

Newsletters

Company Information

Testimonials

Contact Us



ALL STAINLESS STEEL CABINET WITH A LIFETIME WARRANTY

Products >> Single Speed Upflow and Downflow

Small Water to Air
HC18 thru HC72
(1.5 thru 6 ton):

- Standard Water to Air Units
- Single Package
- Available in Upflow, Downflow and Horizontal
- Right or Left Return
- 10, 15, and 20 kW Internal Strip Heat Options
- Domestic Water Heating Option
- 208/230 Volt, Multi-Speed, Direct Drive Fans (with ECM Motor optional)
- High Heating Out-Put
- All Panels Removable for Easy Service



All models in this section qualify for Energy Star except the 6 ton units. Energy Star requires the desuperheater option to qualify.

Forced Air (Water to Air) Single Compressor

ARI 330 Performance Ratings (ISO 13256-1)
Based on 32° entering water temperature in heating mode
and 77° entering water temperature in cooling mode.
(Includes Pump Penalties)

Model #	CFM	GPM	BTU/hr Heating	COP	BTU/hr Cooling	EER
HC18	600	5.0	16,200	3.7	20,000	16.3
HC24	800	6.0	21,300	3.4	25,800	15.5
HC30	1000	7.0	26,700	3.5	32,100	16.0
HC36	1200	9.0	32,000	3.4	38,500	15.8
HC42	1400	11.0	37,300	3.6	46,400	15.7
HC48	1600	12.0	41,800	3.5	50,400	15.4
HC54	1800	13.0	48,000	3.5	57,800	15.4
HC60	2000	14.0	56,200	3.4	65,300	15.0
HC72	2400	16.0	61,000	3.1	72,800	13.5

World's Best Built Heat Pump

E-mail: heatpump@energy-dynamics.com

Copyright © Energy Dynamics 1997-2003; All Rights Reserved.