



[Home](#)

[What is a Ground Source Heat Pump?](#)



[Products](#)

[Construction Features](#)

[Advantages & Benefits](#)

[Training](#)

[Technical Support](#)

[Newsletters](#)

[Company Information](#)

[Testimonials](#)

[Contact Us](#)



ALL STAINLESS STEEL CABINET WITH A LIFETIME WARRANTY

[Products](#) >> Split Systems

**Split System Condensers
HC18S thru HC72S
(1.5 thru 6 ton):**

- Condensing Units Only for Split System Applications
- Water to Air
- Line Set Ready
- Built-in Expansion Valve
- Domestic Water Heating Option
- Same as Condensing Section of Standard HA Series
- May be Used with Fan Coils (below) or with a Matched "A" Coil and Expansion Valve
- High Heating Out-Put
- All Panels Removable for Easy Service



**Split System Fan Coils
HCE18 thru HCE72
(1.5 thru 6 ton):**

- Evaporative Fan Coils for Split System Applications
- Line Set Ready
- Built-in Expansion Valve
- Same as Fan Coil Section of Standard HA Series
- Upflow, Downflow and Horizontal
- Right or Left Return
- 208/230 Volt, Multi-Speed, Direct Drive Fan
- 10, 15 and 20 kW Internal Strip Heat Options



- Matched to Condensing Units Shown Above
- All Panels Removable for Easy Service

Split System Units

Performance Data

Rated in accordance (by Hydron Module LLC) with ISO Standard 13256- which includes Pump Penalties.

Heating capacities based on 70°F DB entering air temperature.

Cooling capacities based on 80°F DB, 67°F WB entering air temperature.

Model #	CFM	GPM	BTU/hr Heating	COP	BTU/hr Cooling	EER
HC18S	600	5.0	16,200	3.7	20,000	16.3
HC24S	800	6.0	21,300	3.4	25,800	15.5
HC30S	1000	7.0	26,700	3.5	32,100	16.0
HC36S	1200	9.0	32,000	3.4	38,500	15.8
HC42S	1400	11.0	37,300	3.6	46,400	15.7
HC48S	1600	12.0	41,800	3.5	50,400	15.4
HC54S	1800	13.0	48,000	3.5	57,800	15.4
HC60S	2000	14.0	56,200	3.4	65,300	15.0
HC72S	2400	16.0	61,000	3.1	72,800	13.5

World's Best Built Heat Pump

E-mail: heatpump@energy-dynamics.com

Copyright © Energy Dynamics 1997-2003; All Rights Reserved.